


PRODUCT LINEUP: VRF

VRF Indoor Units Specifications

Slim Duct / Slim Concealed Floor



Model name			ARXD04GALH	ARXD07GALH	ARXD09GALH	ARXD12GALH	ARXD14GALH	ARXD18GALH	ARXD24GALH
Power source			Single-phase, ~230V, 50Hz						
Capacity	Cooling	kW	1.1	2.2	2.8	3.6	4.5	5.6	7.1
	Heating		1.3	2.8	3.2	4.0	5.0	6.3	8.0
Input power		W	40	44	50	54	92	83	122
Airflow rate	High	m ³ /h	510	550	600	600	800	940	1,330
	Med		400/470* ¹	490	550	510	710	840	1,240
	Low		320/440* ¹	440	480	450	610	750	1,100
Static pressure range		Pa	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 50
Standard static pressure			25	25	25	25	25	25	25
Sound pressure level	High	dB(A)	26	28	29	30	34	34	35
	Med		21/25* ¹	25	26	27	32	32	32
	Low		20/22* ¹	22	24	24	28	28	29
Net Dimensions (H × W × D)		mm	198 × 700 × 620				198 × 900 × 620		198 × 1,100 × 620
Weight		kg(lbs)	17 (37)			18 (40)		22 (48)	26 (57)
Connection pipe diameter	Liquid (Flare)	mm	6.35				9.52		
	Gas (Flare)		12.70				15.88		
Drain hose diameter (I.D./O.D.)			25/32						

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
 Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
 Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m. Voltage : 230 [V].
 *1: This value is under cooling operation.